

Graphic reference



Technical characteristics

Light source : 10 x 0.5 W for main lamp (emergency)
 1 x 1 W for torch
Lumen output : 800 lm for main lamp
 100 lm for torch
Envelope : Polycarbonate
IP / IK : IP54 / IK07
LED temperature : 6500 °K
Working temperature : -10 °C, + 40 °C
Battery : 3.7 V - 4400 mAh Lithium
Power Supply : Charger with USB-C connector:
 Input 100-240V 50-60Hz
 Output 5 Vdc 1000mAh
 Supplied with cigarette lighter adapter
Charging time : 5 hours
Duration : 3 hours for main lamp
 10 hours for torch

Art.nr 605001

Operating characteristics

Charging :

- Charge the lamp with the supplied charger.
- When the lamp is being charged, a red LED is on.
- Once the lamp is properly charged, the LED will turn green.
- Equipped with overload and discharge protection.

Normal operation with ON/OFF switch :

- 1 press : the main lamp lights up.
- 2 presses : the main lamp goes out and the torch comes on.
- 3 presses: both lights are off.

Emergency operation BAPI :

- The lamp must be connected to the mains via the charger.
- When a power failure occurs, the main lamp automatically switches to emergency mode.
- It can then be disconnected from the charger to be used for necessary interventions.
- Once the power has been restored, the lamp can be switched off by pressing the ON/OFF button and then reconnected to its charger.

Fixing options



Belt clip

Hook for suspension

Magnet for fixing on metal base

Support for flat surface